



C105

DEBONDER-SPRAY

An aerosol product with high penetration properties that attacks and dissolves cured or uncured cyanoacrylate adhesive from even most closed surfaces.

FEATURES & BENEFITS

- Easy spray usage,
- It can penetrate into even most closed surfaces where hard to reach the adhesive,
- Does not contain any methylene chloride

APPLICATIONS

- Used in debonding the incorrectly bonded parts or in cleaning the adhesive residues from laminated MDF, metal and some plastics and rubber surfaces in industrial manufacturing environments,
- It can be also used to remove mistakenly bonded body parts like fingers.
- Preliminary test may be needed before using on plastics and paints as Debonder-Gel may be incompatible with certain plastic and paints.

Removes
Bonds with
High
Penetration
Properties

INSTRUCTIONS

- Ensure the application area is clean, dry and free from oil and grease.
- Shake the can well before use.
- Spray on the surface and allow for dissolve cyanoacrylate.
- Performance is dependent on the thickness of the adhesive film to be removed and the substrate it is adhered to.

RESTRICTIONS;

- Use only in well-ventilated areas.
- Keep away from direct sunlight
- Keep away from sources of ignition
- Do not use to debond residues on eyelashes and lips. Since the skin is too sensitive in these areas, sensitization may occur.
- May not be as effective on thick applied adhesive.
- Intended for remove only the cyanoacrylate based adhesives.



STORAGE AND SHELF LIFE;

PROPERTIES

Form	: Aerosol
Appearance	: Clear liquid
Specific gravity	: 0,77 gr/cm ³
Odor	: Characteristic

Performance of the Akfix CA Debonder according to thickness of the Cyanoacrylate film.

THICKNESS* (mm)	1	2	3	5
DEBONDING TIME (min.)	5	7,5	18	46

* It may vary with the any users application style.

PRODUCT

Product Type	Volume	Package

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.